**PCT** WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| (51) International Patent Classification 5 : | | (11) International Publication Number: | WO 92/13430 |
|---|---|---|---|
| H04R 25/00 | A1 | (43) International Publication Date: | 6 August 1992 (06.08.92) |

(21) International Application Number: PCT/US92/00380

(22) International Filing Date: 16 January 1992 (16.01.92)

(30) Priority data:
642,735 17 January 1991 (17.01.91) US

(71)(72) Applicant and Inventor: ADELMAN, Roger, A. [US/US]; 1562 Wittlow Place, Cincinnati, OH 45224 (US).

(74) Agents: LILES, James, D. et al.; Frost & Jacobs, 201 East 5th Street, 2500 Central Trust Center, Cincinnati, OH 45202 (US).

(81) Designated States: AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE (European patent), DK, DK (European patent), ES (European patent), FI, FR (European patent), GA (OAPI patent), GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU (European patent), MC (European patent), MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL (European patent), NO, PL, RO, RU, SD, SE (European patent), SN (OAPI patent), TD (OAPI patent), TG (OAPI patent).

**Published**
*With international search report.*
*With amended claims and statement.*

(54) Title: IMPROVED HEARING APPARATUS

(57) Abstract

A hearing aid is configured and dimensioned so as to be inserted past the cartilaginous part (30) of the external auditory canal (external acoustic meatus) and into the bony part (32) of the external auditory canal. The outer portion of the hearing aid fits snugly into the cartilaginous part (30) of the external auditory canal; the microphone (14) is located at the acoustic focus (36) of the ear such that the natural sound and direction gathering functions of the human outer ear are fully utilized by the hearing aid. The inner portion of the hearing aid is articularly joined to the outer portion to enable the inner portion to be positioned past the sigmoid portion (42) of the external auditory canal and forms a soft covered, elongated speaker (12) which fits within part of the bony part (32) of the external auditory canal, without causing discomfort to the human user.



*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | |
|---|---|---|---|---|---|
| AT | Austria | FI | Finland | ML | Mali |
| AU | Australia | FR | France | MN | Mongolia |
| BB | Barbados | GA | Gabon | MR | Mauritania |
| BE | Belgium | GB | United Kingdom | MW | Malawi |
| BF | Burkina Faso | GN | Guinea | NL | Netherlands |
| BG | Bulgaria | GR | Greece | NO | Norway |
| BJ | Benin | HU | Hungary | PL | Poland |
| BR | Brazil | IE | Ireland | RO | Romania |
| CA | Canada | IT | Italy | RU | Russian Federation |
| CF | Central African Republic | JP | Japan | SD | Sudan |
| CG | Congo | KP | Democratic People's Republic of Korea | SE | Sweden |
| CH | Switzerland | KR | Republic of Korea | SN | Senegal |
| CI | Côte d'Ivoire | LI | Liechtenstein | SU | Soviet Union |
| CM | Cameroon | LK | Sri Lanka | TD | Chad |
| CS | Czechoslovakia | LU | Luxembourg | TG | Togo |
| DE | Germany | MC | Monaco | US | United States of America |
| DK | Denmark | MG | Madagascar | | |
| ES | Spain | | | | |

# IMPROVED HEARING APPARATUS

## TECHNICAL FIELD

The present invention relates generally to hearing aids and listening devices and is particularly directed to a hearing aid that is physically dimensioned and configured to fit inside the external auditory canal (external acoustic meatus). The invention will be specifically disclosed in connection with a miniature hearing aid which has an outer portion located at the acoustic focus of the concha, having a microphone at this important focal point, and which has an inner portion located partially within the bony part of the external auditory canal, having an elongated speaker that is "closely-coupled" to the tympanic membrane.

## BACKGROUND ART

Hearing aids are generally well-known in the art and in wide spread use. In a typical hearing aid, a microphone is used to pick up sound waves and convert that information into electrical signals. An audio amplifier magnifies the electrical signals within the frequencies of interest (20 Hz to 20 KHz), and then sends the amplified signals to a speaker located at the inner portion of the hearing aid. The speaker converts the electrical signals back into sound waves. In technical literature concerning hearing aids, speakers are often referred to as "receivers".

Many conventional hearing aids are relatively large devices that are quite visible to other persons. A recent trend has been to make the hearing

aid as small as possible, and to place a portion of it inside the ear where it is not visible. There are several patents which disclose hearing aids that ostensibly fit within the external auditory canal. It must be noted that, even in such patented inventions disclosing "in-the-canal" hearing aids, a portion of the hearing aid is visible and noticeable to other persons because the speaker and the electronics are too large to fit within the external auditory canal. One exception is disclosed in U.S. Patent No. 4,817,609 by Perkins, wherein the external auditory canal is surgically enlarged so that the disclosed hearing aid can fit deep inside the canal, thereby showing very little to outside observers. Such surgery is an extraordinary remedy that most human users would wish to avoid if a more satisfactory hearing aid were available.

Other U.S. Patents that disclose hearing aids which ostensibly fit within the external auditory canal do not depict the exact anatomy of the external auditory canal. The external auditory canal (external acoustic meatus) leads from the concha (the "bowl" of the ear) to the tympanic membrane (eardrum). The outer one-third of the canal is cartilaginous, and the inner two-thirds is bony. The canal is not straight, but in the horizontal plane (a Transverse Section--see Fig. 3A) it takes a sharp turn, approximately 90°, toward the rear, and then a milder turn back toward the front as the path is traced from the concha toward the tympanic membrane. The area containing these "S-shaped" turns is designated the sigmoid portion of the cartilaginous part of the external auditory canal. Hearing aids that are disclosed as "straight" in overall shape are just not able to be located within the external

auditory canal. Thre patents that disclos such hearing aids are U.S. Patent No. 4,520,236, by Gauthier, No. 4,539,440, by Sciarra, and No. 4,706,778, by Topholm.

The Gauthier patent describes a hearing aid that snugly fits inside the external auditory canal, apparently including the bony part of the canal. The hearing aid appears (from the drawings) to extend the entire length of the auditory canal, virtually against the tympanic membrane; such a device would surely be very uncomfortable to wear. Additionally, the Gauthier patent discloses the use of an earmold that would contain the device. Unless the earmold was very flexible, it would be impossible to insert the hearing aid into its intended location inside the external auditory canal; a "straight" configuration needed to snugly fit into the inner (bony) part of the canal would not be able to be placed through the sigmoid portion of the external auditory canal.

The Sciarra patent describes a hearing aid that has an adjustable diameter, which can be expanded (enlarged) in order to fit snugly inside the external auditory canal. The patent does not disclose precisely where the hearing aid is to sit in the canal. Since the drawings illustrate a "straight" device, it obviously cannot be placed very far into the canal, because it would not be able to make it through the sigmoid portion of the external auditory canal.

The Topholm patent describes a hearing aid that has a hollow space at its innermost tip, which acts as a resonance chamber by enhancing the device's frequency respons in the 1000 Hz to 5000 Hz rang .

The patent does not disclose the location in the external auditory canal wherein the hearing aid is to be placed, nor does it disclose the exact shape of the entire hearing aid. All that is disclosed is a general tubular shape of the innermost tip, and it appears to fit somewhere in the cartilaginous part of the external auditory canal.

Another U.S. patent which discloses a hearing aid that ostensibly fits in the external auditory canal is No. 4,937,876, by Biermans. This patent does not disclose where the hearing aid is to sit in the external auditory canal. The drawings disclose a device which has a "receiver" (speaker) near its innter tip, with such speaker aiming directly toward the tympanic membrane. It is clear, however, that the speaker is too large in diameter to fit through the sigmoid portion of the external auditory canal, and therefore, this invention merely fits into the exterior opening of the external auditory canal with the major portion of hearing aid sticking outside the area of the concha.

It is important to note that, in order to minimize distortion in sound energy transferred to the tympanic membrane, a hearing aid speaker should have a surface area equal or greater than the surface area of the tympanic membrane. Since the surface area of the tympanic membrane is at least as great as an oblique cross-section area of the external auditory canal (as can be seen in FIGS. 3A and 4A of the present invention), it is therefore, obvious that a miniature speaker whose face is pointed directly at the tympanic membrane (as in the Biermans patent) must be at least as large as the cross-section area of the external auditory canal. The inevitable

conclusion is that such a speak r cannot possibly fit past the sigmoid portion of the cartilaginous part of the external auditory canal.

The above four patents attempt to disclose hearing aids that are to be located in the external auditory canal. It is clear, however, from their general shape and size that a major portion of each of these devices must stick out of the ear in a manner that would be visible to others. Either the device is too "straight" to fit past the sigmoid portion of the external auditory canal, and/or the electrical components (including a battery) must reside outside the sigmoid portion of the canal due to their large overall size. Hence, the need for a miniature hearing aid that is small enough and properly shaped to fit deep inside the external auditory canal (without requiring ear surgery) has not yet been met by the above patented devices.

An improvement in the art was disclosed in U.S. Patent No. 4,870,688, by Voroba. The Voroba patent describes a modular hearing aid which is shaped (and sized) to partially fit in the external auditory canal such that a large portion of the device is hidden from view by an outside observer. A portion of the device extends into the inner portion of the canal past the sigmoid portion of the external auditory canal. As the Voroba patent discloses, it is desirable to have the hearing aid extend further into the external auditory canal since the closer the hearing aid is to the tympanic membrane (eardrum), the greater the effective sound output of the hearing aid. The Voroba hearing aid uses a number of "hard" components, having individual geometries which provide for the accommodation of anatomical

variations in individual users. The collection of modular hard parts are at least partially nclosed and extended by a compliant covering. The covering of the inner portion of the Voroba hearing aid is made of soft (compliant) material, and it may penetrate up to 3/4 of the length of the external auditory canal, thereby increasing the effective gain of the hearing aid by 6 to 10 dB over conventional "in-the-canal" hearing aids.

It must be noted, however, that the Voroba invention does not place its speaker at the innermost portion of the device. The speaker is, instead, located further toward the outer portion of the device (approximately in the center of the device according to the drawings), and a sound-carrying tube, surrounded by soft, resilient material, extends to the innermost tip of the device. In effect, the speaker (called a "receiver" in the Voroba patent) emits sound waves into the tube, and the tube acts as a passive wave guide toward the inner portion of the external auditory canal, and toward the tympanic membrane. The Voroba patent, therefore, only teaches the concept used in the prior art of having passive elements in the innermost portion of the hearing aid. Such passive elements are merely space-consuming conduits which transfer the acoustic energy from the active, sound-generating surface of the speaker. The air inside such passive element is compressible, so this system still lacks a certain amount of efficiency, and compromises the faithful reproduction of the soundwave at the tympanic membrane. In essence, the overall system of hearing aid speaker to tympanic membrane is not "closely-coupled."

Clos coupling of an acoustic sourc to the tympanic membran is necessary for the realization of the beneficial attributes gleaned by signal processing for the treatment of hearing deficit. Devices in the prior art for generalized signal processing, including U.S. Patent No. 4,637,402 by Adelman, and Patent Numbers 4,882,762, and 4,882,761 by Waldhauer, demonstrate optimization techniques for manipulating the electronic representation of the audio signal, but fail to provide optimal presentation as a sound wave to the tympanic membrane. Thus, generalized signal processing techniques of the prior art are limited by the ability of the output transducing device (the speaker) and, therefore, are not closely coupled systems.

To achieve a more closely-coupled system, the amount of compliant material between the active face of the speaker and the receptive face of the tympanic membrane must be kept to a minimum. The best method to achieve such a system is to reduce the volume of air (thereby reducing the amount of compliant material) contained in the active path of the sound waves. The beneficial effects of such a system are (1) better bandwidth, (2) greater efficiency of energy transmission, and (3) reduced distortion of the auditory signal. A better method for achieving such a closely-coupled system is to locate the active speaker itself inside the external auditory canal, as close to the eardrum as feasible, while also keeping the amount of compliant material (the amount of air volume) in the system to a minimum.

## SUMMARY OF THE INVENTION

Accordingly, it is a primary object of the present invention to provide a hearing aid that is properly shaped, sized, and oriented to fit within the external auditory canal, causing the speaker element to fit in the canal at a point between the sigmoid portion of the canal and the tympanic membrane.

It is another object of the present invention to provide a hearing aid that is properly shaped, sized and oriented to fit within the external auditory canal, with the speaker element located in the canal between the sigmoid portion of the canal and the tympanic membrane, whereby the hearing aid is covered by a disposable boot that prevents contamination and seals the external auditory canal so that the volume of air between the hearing aid and the tympanic membrane is held constant.

It is yet another object of the present invention to provide a hearing aid that is properly shaped, sized, and oriented to fit within the external auditory canal, whereby the speaker element has an elongated shape so as to not only fit deeply in the canal between the sigmoid portion of the external auditory canal and the tympanic membrane, but also to allow the speaker to exhibit a "high-fidelity" frequency response in the human hearing range of 20 Hz to 20 KHz, and to minimize distortion.

A further object of the present invention is to provide a hearing aid which has an inner portion that is prop rly shaped, sized, and oriented to fit within the external auditory canal, whereby the out r

portion (the microphone and the electrical, electronic, and signal processing components) may be miniaturized to an extent that, while it is in use, the outer portion of the hearing aid is barely noticeable to another person who is observing the user.

A yet further object of the present invention is to provide a hearing aid which has an inner portion that is properly shaped, sized, and oriented to fit within the external auditory canal, whereby the microphone in the outer portion is located at the acoustic focus of the concha, thereby utilizing the natural sound gathering and direction locating anatomical features of the human ear to the greatest possible extent.

A still further object of the present invention is to provide a hearing aid that is properly shaped, sized, and oriented to fit within the external auditory canal, whereby the external tip of the hearing aid at the microphone contains a large on-off control which can be actuated by the fingertip of the human user, and can also be used as a volume control, and a "treble-bass" filter control.

It is yet another object of the present invention to provide a hearing aid that is properly shaped, sized, and oriented to fit within the external auditory canal and has its microphone at the acoustic focus of the concha, whereby a hand-held transmitter is used to adjust the volume level and the treble-bass filter of the hearing aid. Such a hand-held transmitter could use radio frequency electromagnetic radiation to carry the necessary information to th hearing aid, or it could use other

wav lengths of el ctromagnetic radiati n to carry the information, such as ultraviol t, infrared, or microwave frequencies. Ultrasonic sound waves could even be used to perform the above task.

It is still another object of the present invention to provide a hearing aid that is properly shaped, sized, and oriented to fit within the external auditory canal and has its microphone at the acoustic focus of the concha, whereby a radio link is also used to provide signal processing by a remote computer linked to the hearing aid. Such signal processing can be used to enhance certain frequencies, remove background noise, or to remove other unwanted sound patterns.

A still further object of the present invention is to provide a hearing aid that is capable of amplifying or attenuating the conductive sound (conducted through the bones) that is created by the human user's own voice.

A yet further object of the present invention is to provide a hearing aid that is properly shaped, sized, and oriented to fit within the external auditory canal, and to combine a radio receiver as an input to the amplifier such that the hearing aid speaker would output both information received from a radio station, and sound wave information received by the hearing aid input microphone (at a reduced volume, if desired). Such received radio frequencies could be in the commercial AM and FM bands.

Additional objects, advantages and other novel f atur s f th invention will be set forth in part in th d scription that f llows and in part will

become apparent to those skilled in the art upon examination of the following or may be learned with the practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

To achieve the foregoing and other objects, and in accordance with the purposes of the present invention as described herein, an improved hearing aid is provided having substantially small overall size and the correct shape to fit in the external auditory canal of the human ear. The speaker element of the hearing aid is placed within the canal at a point between the sigmoid portion of the canal and the tympanic membrane. The hearing aid is covered by a disposal boot that prevents contamination of the functional parts of the hearing aid and seals the external auditory canal around the hearing aid so that the volume of air between the hearing aid and the tympanic membrane is held constant. The central portion of the boot consists of a deformable material, so that one size of hearing aid will fit most human users. This deformable material tends to retain its original size and shape, such that it will press snugly against the inner diameter of the external auditory canal of the user's ear, particularly at the entrance to the external auditory canal. This deformable material seal also serves as a sound insulator which prevents feedback from the speaker to the microphone of the hearing aid.

The fact that the deformable boot tends to seal the volume of air inside the external auditory canal, between the point that the hearing aid makes contact

with th inner membrane of the us r's ear and the tympanic membrane, is important to achieve a closely-coupled system. As discussed above, to achieve a closely-coupled system, the amount of compliant material between the active face of the speaker and the receptive face of the tympanic membrane must be kept to a minimum. By sealing the volume of air inside the overall system that consists of the hearing aid, the air column, and the tympanic membrane, the amount of compliant material (the air) is minimized and kept constant, so that motion at the speaker is accommodated only by a responsive motion of the tympanic membrane, along with avoiding unwanted resonances in the small volume of trapped air.

In accordance with a further aspect of the invention, the speaker element of the hearing aid has an elongated shape so as to not only fit in the external auditory canal between the sigmoid portion of the cartilaginous part of the external auditory canal and the tympanic membrane, but also to have a large enough surface area to cause a sympathetic vibration of the tympanic membrane. Such large sound generating surface enables the speaker to produce sound energy which is largely devoid of harmonic distortion in the normal human hearing range of 20 Hertz to 20 Kilohertz. The overall cross sectional shape of the speaker element is generally that of a flattened tube. The acoustic output of the speaker is created by a speaker membrane which is driven by an electromagnetic linear motor. In one embodiment, the linear motor consists of a permanent magnetic field and an oval-shaped current-carrying coil which is disposed within the magnetic field. The coil is p rmanently affixed to th speaker m mbrane (its

fac ), forming an armature. A portion of the speak r structure consists f one or mor resonanc cavities on the interior of the speaker membranes tunably suitable for the enhancement of certain portions of the frequency spectrum. The speaker must consist of at least one armature that forms the speaker's face, however, in a second embodiment, there are two separate faces, on opposite sides of the speaker. Each of these two faces may have its own resonance cavity and its own compliant properties, thereby allowing each speaker face to be used for the enhancement of a different portion of the frequency spectrum, such as treble or bass.

According to a further aspect of the invention, the speaker membrane is in the form of an oval plane and has compliance enhancing ripples near its attachment edges. A substantial portion of the plane is movable as a rigid body, yet the ripples near its attachment edges greatly enhance the performance of the speaker in the form of greater efficiency.

In yet a further aspect of the invention, the overall speaker portion of the hearing aid is articulated at its attachment point to the rest of the main body of the hearing aid. This allows the speaker element to fit past the sigmoid portion of the external auditory canal, and thereby allows the entire speaker to fit inside the canal.

In yet another aspect of the invention, the remaining components of the hearing aid, i.e., the microphone and the electrical components, are miniaturized to the extent that the entire hearing aid is barely visible to another person who is obs rving the user. This is made possibl by

constructing the hearing aid such that the entire speaker element fits inside the external auditory canal, and the portion of the hearing aid that contains the battery and the electronic components fits at the very entrance of the canal, such that the microphone is located at the acoustic focus of the concha. As discussed above, the shape of the hearing aid and the configuration and orientation of its elements is very important so that the desired location of its placement in a human ear is possible. As practiced by this invention, the entire hearing aid is substantially out of sight of another observer, except for the microphone itself, which is at the very entrance of the external auditory canal (i.e., at the acoustic focus of the concha). By locating the active elements of the entire hearing aid deeper in the external auditory canal, the hearing aid does not protrude out from the concha, and therefore, cannot be seen by others.

In yet another aspect of the invention, the microphone is located at the acoustic focus of the concha. This arrangement maximizes the natural sound gathering and direction locating anatomical features of the human ear. Since the concha (the "bowl" of the ear) is naturally designed to be the focal point of sound entering the human ear, its acoustic focal point is also the logical location for a microphone of a hearing aid. Until the present invention, however, no hearing aid has been able to place the microphone specifically at this point. While the type of microphone used in this invention is not crucial, it must, however, be small in size in order to fit inside the concha, and it should also operate using little electrical power. Two microphones technologies that have been successfully utilized in

this invention are the electret, and the piezoelectric types.

In a further aspect of the invention, the electronics of the hearing aid include volume and tone (treble - bass) functions. The volume function can have an automatic gain control circuit, and the gain of the electronics can either be linear or non-linear, as necessary, to minimize or eliminate distortion.

In accordance with yet another aspect of the invention, the external prominence of the hearing aid, essentially at the location of the microphone, contains an on/off control which can be actuated by the fingertip of the human user. Fingertip actuation of this control also provides a volume control and treble-bass filter control in one embodiment.

In accordance with a still further aspect of the invention, a hand-held transmitter is used to adjust the volume level and the treble-bass filter of the hearing aid. In one embodiment the hand-held transmitter uses radio frequency electromagnetic radiation to carry the necessary information to the hearing aid. In a second embodiment, the transmitter uses electromagnetic radiation in the infrared frequency spectrum to carry the necessary information to the hearing aid. It is obvious that any safe frequency of electromagnetic radiation could be used to carry the necessary information to the hearing aid over the short range required. Ultrasonic sound waves could even be used to perform this task.

According to yet another aspect of the present invention, a single-part hearing aid (which includes

substantially the same lements as in the single-part h aring aid d scribed abov ) is combined with a self-contained enhanced signal processing unit. Such enhanced signal processing can remove background noise, enhance certain frequencies, or remove other unwanted sound patterns. This aspect of the invention can be utilized to greatly enhance the performance of the hearing aid for persons having particularly profound hearing dysfunction.

According to a yet further aspect of the invention, a radio link is used to provide enhanced signal processing to the hearing aid. Such signal processing is performed by a remote signal processing unit which can be used to enhance certain frequencies, remove background noise, or also to remove other unwanted sound patterns. The radio link would be best utilized as a simultaneous two-way link (full duplex) whereby the original sound is captured by the microphone of the hearing aid portion of this system (which consists of substantially the same elements as in the single-part hearing aid described above), then transmitted by the radio link to the signal processing portion of this system. The signal processing portion can be a portable unit, strapped to the user's clothing, or it can be a stationary unit for non-mobile use. After processing, the information is retransmitted from the signal processing portion by radio link back to the hearing aid portion for transfer to the speaker output of the hearing aid. This remote enhanced signal processing portion is available when the electronic elements are too large in size, or are too great in electrical power consumption to fit within the anatomical limitations of the abov -described single part hearing aid. This asp ct of th inventi n can be

utilized to greatly enhance the performance of the hearing aid for persons having particularly profound hearing dysfunction.

According to a still further aspect of the invention, use of an accelerometer or other rigid body motion sensing device cancels or enhances the conductive sound that is created by the human user's own voice. Such sound waves are conducted through the solid structure of the speaker's head into the temporal bone, which conducts the sound waves directly into the cochlea of that speaker's ear. Depending upon the hearing needs of the particular user of the hearing aid, such conductive sound would be best enhanced or attenuated by the hearing aid. In this aspect of the invention, the accelerometer or other rigid body motion sensor is attached to the surface of the hearing aid at a point where it most closely comes in contact with the solid portion of the external auditory canal. In this way, the accelerometer can sense directly the conductive sound waves created by the human user's own voice. Such sound waves would then be either amplified or attenuated, and then mixed with air-borne sound detected by the microphone according to the user's needs. The degree of amplification, attenuation, or mixing could be controlled by the previously mentioned hand-held transmitter, or through a separate control that the user could actuate with his fingertip.

In yet a still further aspect of the invention, a radio receiver is also placed inside the hearing aid such that the hearing aid speaker would output information received from both the radio station, and sound wave information received by the hearing aid

input microphone. The most common set of radio frequencies that would be received would be the commercial AM and FM bands of frequencies. Once again, it would be desirable to be able to adjust the volume of the received radio frequencies independent of the volume received by the microphone. Such volume controls could be located in the previously mentioned hand-held transmitter, or by a fingertip control.

In accordance with another aspect of the invention, no external air vent is required to tune the acoustical pathway between the speaker and the eardrum. The possibility of "whistling," because of feedback from the speaker to the microphone, via that type of conduit is entirely eliminated. Very high amplification is thus possible in a miniaturized hearing aid that fits in the external auditory canal without the bothersome quality of "whistling."

Still other objects of the present invention will become apparent to those skilled in this art from the following description wherein there is shown and described a preferred embodiment of this invention, simply by way of illustration, of one of the best modes contemplated for carrying out the invention. As will be realized, the invention is capable of other different embodiments, and its several details are capable of modification in various, obvious aspects all without departing from the invention. Accordingly, the drawings and descriptions will be regarded as illustrative in nature and not as restrictive.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings incorporated in and forming a part of the specification illustrate several aspects of the present invention, and together with the description serve to explain the principles of the invention. In the drawings:

FIGS. 1A-1E show several views of the complete hearing aid device constructed in accordance with the principles of the present invention;

FIG. 1A is a cross-sectional elevation view of the entire device constructed in accordance with the principles of the present invention;

FIG. 1B is a top plan view of the hearing aid device of FIG. 1A;

FIG. 1C is an elevational view of the hearing aid device of FIG. 1A, showing the details of a disposable boot in cross-section, including its deformable material portion;

FIG. 1D is a partial cross-sectional view taken along line 1D-1D of FIG. 1A;

FIG. 1E is a bottom plan view of the hearing aid device of FIG. 1A, illustrating a loop antenna in the base;

FIG. 2 is an oblique view of a human head, showing the anatomical sections designated as the coronal section, and the transverse section;

FIG. 3A shows the correct anatomical view of the transverse section of the human ear, taken along line 3-3 in FIG. 2;

FIG. 3B shows the same view as FIG. 3A, however, it includes the placement of the hearing aid device;

FIG. 4A shows the correct anatomical view of a coronal section of the human ear, taken along line 4-4 in FIG. 2;

FIG. 4B shows the same view as FIG. 4A, however, it also includes the placement of the hearing aid device;

FIGS. 5A-5C show the details of the speaker portion of the hearing aid device of FIG. 1A;

FIG. 5A is a plan view of the speaker portion of the hearing aid device of FIG. 1A, and a cross-sectional view of its articulated joint;

FIG. 5B is a longitudinal cross-section view of the speaker portion, taken along line 5B-5B of FIG. 5A;

FIG. 5C is a sectional view of the speaker portion, taken along line 5C-5C of FIG. 5B;

FIGS. 6A-6C show the details of the outer cover of the hearing aid device of FIG. 5A;

FIG. 6A is a plan view of the speaker cover of FIG. 5A;

FIG. 6B is a cross-sectional elevation view of the speaker cover, taken along line 6B-6B of FIG. 6A;

FIG. 6C is a cross-sectional elevation view of the speaker cover, taken along line 6C-6C of FIG. 6A;

FIGS. 7A-7C show the details of the armature of the hearing aid device of FIG. 5A;

FIG. 7A is a plan view of the speaker armature of FIG. 5A;

FIG. 7B is a cross-sectional elevation view of the armature, taken along line 7B-7B of FIG. 7A;

FIG. 7C is a cross-sectional elevation view of the armature, taken along line 7C-7C of FIG. 7A;

FIGS. 8A-8C show details of the microphone using an electret device;

FIG. 8A is a top plan view of a microphone used in the hearing aid device of FIG. 1A;

FIG. 8B is a cross-sectional elevation view of the microphone of FIG. 8A;

FIG. 8C is an enlargement of the upper right hand corner portion of FIG. 8B;

FIGS. 9A-9C show an alternative microphone using a piezo electric device;

FIG. 9A is a top plan view of an alternative microphone for the hearing aid device of FIG. 1A;

FIG. 9B is a cross-sectional elevation view of the microphon of FIG. 9A;

FIG. 9C is an enlargement of the upper right hand corner portion of FIG. 9B;

FIG. 10 shows an accelerometer, used in the hearing aid device of FIG. 1A;

FIG. 11 is an electrical schematic of the hearing aid device of FIG. 1A having local controls.

FIG. 12 is an alternative electrical schematic of the hearing aid device of FIG. 1A, in this case, having a remote hand-held controller which communicates to the hearing aid device;

FIG. 13 is another alternative schematic for the hearing aid device of FIG. 1A which, in addition to what is described in FIG. 12, also has a accelerometer input;

FIG. 14 is another alternative electrical schematic that shows a signal processing unit which is remote to the hearing aid, and is in constant communication with the hearing aid device of FIG. 1A;

FIG. 15 is an electrical schematic which shows a remote hand-held device which communicates with the hearing aid device of FIG. 1, which in addition, contains a radio receiver.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, a preferred embodiment of th hearing aid device 10 is shown,

containing a sp ak r portion 12,. a microphone portion 14, and a main body portion 16. Several views of these portions of the hearing aid device 10 are illustrated in FIGS. 1A-1E. FIG. 1B shows a preferred location for the electronic components of the device 10. An integrated circuit which makes up an accelerometer is illustrated shown as an electronic chip 50. An integrated circuit which contains the amplifiers and any transmitter and receiver components is illustrated as an electronic chip 52. A third electronic chip 51 for a third integrated circuit is disposed between chips 50 and 52, and can be used for additional transmitter components, as well as any desired supplemental signal processing circuitry. Electrical connections from the speaker and microphone portions 12 and 14 to the electronic components are preferably made at the connection of electronic chip 51.

As illustrated in FIG. 1C, the hearing aid 10 is covered with a disposal boot 20, which is made of an open cell deformable foam material which has a memory. The portion 21 of the disposable boot 20 which fits over the speaker portion 12 is very thin, in the order of 1mm, and is shown with an exaggerated thickness in FIG. 1C for purposes of illustration. One of the functions of the disposable boot 20 is to seal the air inside the external auditory canal so that it cannot escape nor can any atmospheric air enter that area, once the hearing aid 10 is in place. This is accomplished by increasing the thickness of the boot 20 in the portion 22 surrounding the articulated joint 102. Another function of the disposable boot 20 is to prevent contamination of the hearing aid by acting as a shield against y wax, (cerum n) and other

exfoliants of the epithelium of the ear canal. Another feature of the disposable boot 20 is a pull-off tab 24 which allows the user to grip that portion of the disposable boot and pull the entire hearing aid out from the user's ear.

As most clearly shown in FIG. 1D, the hearing aid device 10 uses a power source, which in the preferred embodiment comprises two batteries 54. The batteries 54 of the preferred embodiment are of the type 377 and are not connected in series, but are instead used to provide a bipolar DC power source for the electronics of the hearing aid. It is obvious that other DC power sources could be used in lieu of the batteries 54.

A detail of the loop antenna 78 is illustrated in FIG. 1E. Such loop antenna 78 could be used for any radio frequency transmitter or receiver devices that might be used in conjunction with the hearing aid 10.

In order to understand the significance of several aspects of this invention, it is necessary to fully appreciate the precise anatomy of the human ear. FIG. 3A is an anatomically accurate, transverse section of the human ear showing the important structural details relevant to the present invention. Starting at the exterior point of the ear, the curved surface of the concha 41 is illustrated in the region bounded by the bracketed lines 40 in the illustration of FIG. 3A. The acoustic focus of the concha 41 is located at the point identified by the numeral 36. The point 36 is the location where the natural shape of the human ear focuses incoming sound waves. The external auditory canal is formed by two distinct portions. The outer

m st portion of the external auditory canal, called the cartilaginous part of the external auditory canal, is the portion enumerated 30 between the two bracketed lines. The innermost portion of the external auditory canal is called the bony part of the external auditory canal 32, and lies between the innermost two bracketed lines. The tragus 38 lies at the entrance to the external auditory canal opposite the concha 41. The sigmoid portion of the cartilaginous part of the external auditory canal is the S-shaped dashed line identified by the numeral 42. The average inner diameter of the external auditory canal is approximately 7 mm. At the innermost portion of the external auditory canal lies the tympanic membrane 34, which is also called the eardrum. The effective surface area of the tympanic membrane lies in the range of 30-35 square mm.

The same anatomical features of the human ear are again accurately depicted in FIG. 4A, however, FIG. 4A is a coronal section of the human ear, which is 90° from the transverse section of FIG. 3A.

FIG. 3B depicts the hearing aid device 10 positioned in the human ear. As can be seen in FIG. 3B, the main body portion 16 of the hearing aid 10 is located directly at the entrance of the external auditory canal. The main body position 16 lies in contact with, and is hidden from view by the tragus 38. The microphone portion 14 of the hearing aid 10 is advantageously located such that it is directly at the acoustic focus of the concha 36 so that it maximizes the natural sound gathering and direction locating anatomical features of the human ear. The speaker portion 12 of the hearing aid is located entirely inside the external auditory canal, and it

fits past the sigmoid portion 42 of th cartilaginous part of th xternal auditory canal. Quite significantly, the speaker portion 12 is designed to fit entirely inside the external auditory canal, yet has a large enough surface area of active speaker element to effectively vibrate the human tympanic membrane 34.

The same elements of the hearing aid device 10 are described in the companion view, FIG. 4B, which is a coronal section of the human ear. Again, the microphone portion 14 of the hearing aid is located at the acoustic focus of the concha 36, and the speaker portion 12, which is clearly shown in this view, is located entirely inside the external auditory canal well past the sigmoid portion.

The speaker portion 12 of the hearing aid device 10 consists largely of a linear motor 100, which is described in detail in FIGS. 5A-5C. The top cover 112 of the linear motor 100 consists of magnetically permeable material. There are a number of air holes 104 of different sizes in the top cover 112. In the embodiment of FIG. 5B, there is also a bottom cover 152, also consisting of magnetically permeable material, and is constructed similarly to the top cover, also having air holes (not shown). The entire linear motor 100 is held together and surrounded by an outer housing 140. In the preferred embodiment of FIGS. 5A-5C, the outer housing 140 is made of shrinkable plastic material. The outer housing 140 is pressed around the outer pole piece 132, which is also called a banjo housing. The outer pole piece 132 is made of magnetically permeable material; in th pref rred mbodim nt it is made of soft steel. The out r pole piece 132 xtends through the ball of

the articulated joint 102, and is hollow in that region, acting as a conduit for the electrical conductors 118 that lead to the speaker coils 116 and 148. The articulated joint 102 allows the speaker portion 12 to pivotally move in relation to the main body portion 16, which allows the speaker portion 12 to easily fit in the external auditory canal.

The top speaker membrane 114 consists of a three micron polyester film having a surface area at least equal to the effective surface area of the tympanic membrane, i.e., approximately 32 square mm in the preferred embodiment. The elongated oval shape and construction of the top speaker membrane 114 is also disclosed in FIGS. 7A-7C. The top coil 116 is rigidly affixed to the top speaker membrane 114 at attachment edges 120. To make the speaker more effective, compliance enhancing ripples 124 are formed in the top speaker membrane 114. An additional feature to make the speaker more effective is the curved pleats 122 in the material of the top speaker membrane. These pleats 122 are formed by serrating the mold for the top speaker membranes, and they enhance further the compliance of the top speaker membrane 114. The top speaker coil 116 consists of 15 turns of oval shaped windings, and is constructed of Number 48 AWG coated copper magnet wire. The coating consists of a polymeric insulation material and a secondary rubberized plastic shape-holding material. The top spacer ring 144 holds the very outer edges of the top speaker membrane 114 in place, and consists of metallic material such as brass. The top armature of the linear motor includes the top speaker membrane 114, the top coil 116, and the top spacer ring 144.

The bottom speaker armature consists of the same types of components and materials as does the top speaker armature. In the case of the bottom armature, there is a bottom speaker membrane 150, a bottom coil 148, and a bottom spacer ring 154. The materials of the bottom armature are virtually the same as that of the top armature, however, certain features may be varied to achieve a tweeter-type speaker on the top (having enhanced treble response), for example, and a woofer-type speaker on the bottom (having enhanced bass response). Such features that could be varied are those that affect the mass, spring and damping characteristics of the armature, such as the thickness of the speaker membranes, the number of windings of the coil, and the size of the magnet wire which makes up the coil, and also the size and shape of the resonance cavities. The top speaker resonance cavity is identified by the numeral 126, and the bottom speaker has a similar resonance cavity identified by numeral 156, which is larger in size (volume) for enhanced bass response in the illustrated embodiment. The control gap 130 can be used to vary the amount of air that can be exchanged between two resonance cavities 126 and 156.

The linear motor 100 additionally consists of a permanent magnet 136, and a magnet support piece 134. The permanent magnet of the preferred embodiment consists of Neodimium-Boron-Iron, or Samarium Cobalt. Neodimium-Boron-Iron can exert a stronger magnetic field than Samarium-Cobalt, however, Samarium-Cobalt will not rust.

The attachment edges 120 are node points for the attachment of the coils to the speaker membranes. This attachment is made by a rubber-based glue. The

speaker of the pref rred embodiment, as described above, is a moving coil circuit, wher as prior art small hearing aid speakers generally have used variable reluctance circuits, which generally have given poor low frequency performance.

The microphone portion of the hearing aid 10 is detailed in FIGS. 8A-8C and 9A-9C. The embodiment illustrated in FIGS. 8A-8C uses an electret type microphone. Forming an outer housing for the microphone is the microphone cover 160. This cover can be made of formed metal, such as aluminum, or formed plastic. Just inside this cover is a first spacer 162, which consists of a material which is electrically nonconductive. This spacer is used to maintain a gap between the microphone cover 160 and the microphone diaphragm 164. The microphone diaphragm consists of a permanently charged material, such as metallized film or metallized polyester. On the other side of the microphone diaphragm 164 is a second spacer 166 which consists of a material which is electrically nonconductive. The second spacer 166 maintains the quiescent gap between the microphone diaphragm 164 and the plate 168.

The plate 168 consists of conductive metal, such as nickel plated copper, or steel. The plate 168 rests on top of the mounting block 172, and also is attached to the gate 176 of a field effect transistor 174. The mounting block 172 is formed of electrically nonconductive material such as plastic. The mounting block contains a provision 170 for venting the gap which is inside the second spacer 166 and is between the microphone diagram 164 and the plate 168. The field effect transistor 174 also has a source 178 and a drain 180, and with a pair of

wires 182 attached, one to the gate and one to the source. Such electret microphone assemblies 184 are available in the prior art, such as one made by Panasonic having a part number WM-6A.

The microphone portion 14 illustrated in FIG. 8 also consists of two potentiometers and the on/off switch. The on/off switch consist of a conductive ring 190 which has a gap for the off portion of the ring. The turning of the microphone cover 160 actuates this on/off switch. The treble-bass filter control consists of a first potentiometer. The first potentiometer has a ring of resistance film media 194, which is not necessarily uniform, and a rotatable wiper 196. The first potentiometer media 194 is physically located and held in place by a nonconductive support 198. The rotatable wiper 196 is only engaged to rotate when the actuator 210 is depressed while being rotated. The actuator 210 is forced down when the microphone cover 160 is depressed. The support structure 192 is the overall housing base for maintaining the potentiometers in place while the microphone cover 160 is being depressed.

A second potentiometer controls the volume of the hearing aid. This second potentiometer consist of a ring of resistance film media 202, a rotatable wiper 204, and physical support which consists of a nonconductive support 206. The second potentiometer operates in the opposite sense as the first potentiometer in that its rotatable wiper 204 is actuated when the actuator 110 is not depressed. When the actuator 210 is not depressed, the spring 212 keeps tension on the rotatable wiper 204, and allows it to be rotated. To effectively communicate

electrical information to the control means, the potentiometers and the on/off control must have conducting means such as wires attached to them. A pair of wires 200 runs to the first potentiometer, a second pair of wires 208 runs to the second potentiometer, and a third pair of wires 214 runs to the on/off ring.

A piezo type microphone can alternatively be used rather than the electret type microphone. In the embodiment of FIG. 9, the microphone cover 220 is approximately the same size as the electret microphone cover 160. In this case, the microphone cover 220 must be made out of a material which is electrically nonconductive. Just beneath the microphone cover 220 is the first spacer 222. This first spacer consists of an electrically conductive material, and is connected by a wire to the positive input of the microphone transducer amplifier. Below (on the other side of) the first spacer 222 is the microphone diagram 224. This diagram consists of a material called Kynar, which is made by Pennwalt Corporation. On the other side of the microphone diagram 224 is a second spacer 226. This second spacer is also made of an electrically conductive material, and is connected to the negative input of the transistor amplifier. The two spacers 222 and 226 plus the microphone diagram 224 rest on the mounting block 228, and have two wires 232 attached to the two spacers (one wire per spacer). In the embodiment of FIG.9, there is no field effect transistor and there is no plate. The remaining parts of the microphone portion of the embodiment of FIG. 9B are precisely the same as that shown in FIG. 8B.

One embodiment of th hearing aid can consist of an optional acc lerometer assembly 248. Th accelerometer is used to either enhance or attenuate the conductive sound of the user's voice through the user's bones into the cochlea of the ear. These conductive sound waves travel through the temporal bone which completely surrounds the inner ear, and directly excite the mechnoneural sensory structures within the inner ear. Conductive sound is present in the normal ear, and its magnitude is normally balanced with the air-borne portion of one's own voice. However, such conductive sound, if existing at a large magnitude, can be very distracting to the user, in which case the accelerometer signal would be attenuated. If it is absent in yet other users it causes a distorted perception of the user's own voice, and in which case the accelerometer signal would be amplified. The accelerometer assembly 248 is built on the integrated circuit 50 in the main body portion 16 of the device. The general layout of the accelerometer is given in FIGS. 10A-10B, which shows the substrate 240 and the seismic mass 242. The substrate can be made of silicon, as used in the substrate for integrated circuits. The seismic mass 242 would consist of a high density material, such as copper. Sensing elements 244 are laid out on the substrate 240 and consist of materials having electrical characteristics which are sensitive to strain. The nodes 246 are enlarged pads so as to more easily make electrical connection to the accelerometer assembly 248. The entire accelerometer assembly 248 is built onto the integrated circuit 50, and is physically isolated from the microphone and the speaker. The accelerometer is, therefore, not s nsitiv to air-borne sound waves, but only bone-conducted sound waves.

It is obvious to on skilled in the art that the acc l rom ter n d not consist of a seismic mass 242 mounted on a strain gauged beam (substrate 240) as described above. Other types of accelerometers having similar size and construction could be used in the alternative. Such other types of accelerometers could consist of a mass 242 mounted on the movable portion of a charged membrane 240, or a mass 242 mounted on a piezoelectric beam 240 (called a piezo bimorphic). The major difference between the different types of accelerometers is the material used for the beam (the substrate 240), the nature of the sensing elements 244 which are attached to the beam 240, and the signal conditioning electronics required among the various types.

The electrical schematic in block diagram form of a stand alone hearing aid 10 is given in FIG. 11. The control means 216 consists of three control devices which are a part of the microphone portion 14. The three controls included in control means 216 are the on/off switch, the volume control potentiometer, and the treble-bass filter potentiometer. FIG. 11 uses an electret microphone 184, however, it should be recognized that any type of miniature microphone could be used in this application. The sound energy is transformed by the microphone 184 into electrical signals which are passed into the input microphone transducer amplifier 260. After initial amplification, the electrical signal is then passed into a set of amplifiers which act as a treble-bass filter and an intermediate gain amplifier 262. This treble-bass filter and intermediate gain amplifier 262 communicates with the control means 216 so as to properly control the h aring aid as per the user's wishes. Any automatic

gain control functions, whether linear or non-linear in profile, are performed by the intermediate gain amplifier 262. The output of the treble-bass filter and the intermediate gain amplifier 262 is then communicated to an output power amplifier 264. The power amplifier 264 has as its output stage a class B push-pull dual transistor output. By use of a dual DC voltage power supply (supplied by two DC batteries 54), all of the amplifiers in the hearing aid can run in a bipolar configuration, including the power amplifier. By effective use of this bipolar DC power supply, the power amplifier 264 can use push-pull transistors on its final output stage, and eliminate any typically large valued bypass capacitors that would otherwise be required. The output signal of the power amplifier 264 is then communicated to the speaker, which consists of the linear motor 100.

The above amplifiers, including the output stage power amplifier, are all located on the integrated circuit 52. Some of the low-gain amplifier stages use an operational amplifier such as the OP-90, manufactured by Precision Monolithics. The OP-90 is available on a semi-custom chip, or can be, of course, placed on a custom analog chip.

Another embodiment of the invention uses a hand-held transmitter to control the user's input commands to the hearing aid. In FIG. 12 the hand-held transmitter is designated 70, and consists of an operator interface 266, a controller 268, and a transmitter 72. The operator interface 266 could be a key pad, a miniature keyboard, or even an existing design TV remote controller, so that the user can hit certain control keys to adjust the volume control of the hearing aid, or to adjust the treble-base

filter. The controller 268 is typically a small microprocessor unit which communicates through the operator interface 266 and then passes commands in a digital code signal format to the transmitter stage 72. The transmitter stage 72 can be of various types.

The various types of transmitters which can be used are as follows: a radio frequency transmitter, which would require some type of antenna built into the hand-held unit, or an infrared transmitter, which would require an infrared light emitting diode, or possibly an ultrasonic transmitter means, which would require some type of high frequency speaker output. Whichever means of communication is utilized, it is designated as 76 on FIG. 12.

The communication means 76 requires a corresponding receiver 74, which is in the hearing aid device 10. The receiver 74 converts the communication signal to electrical signals, which are then passed to the control means 270. The control means 270 is similar in function to the previously discussed control means 216 of FIG. 11, in that it controls the treble-base filter and intermediate gain amplifier 262 of the hearing aid 10. Also included as part of the control signals is a local on/off control function 190. The local on/off control 190 is needed to allow the user to completely turn off electrical power in the hearing aid device 10. As in the previous embodiment, the microphone 184 receives sound energy and converts it to electrical energy, which is passed to the microphone transducer amplifier 260. The output of the transducer amplifier 260 is communicated to the filter and gain amplifier 262, which is now controlled by control means 270, which utilizes the received information

from th receiv r 74. Th electrical signal is th n sent to the pow r amplifier 264, and finally to the speaker element 100. To be effective, the receiver 74 requires an antenna 78.

Another embodiment of the hearing aid which uses a hand-held transmitter 70 is shown in FIG. 13. This embodiment also includes an accelerometer 248, to either add or subtract conductive sound information. As before, the hand-held transmitter 70 consists of an operator interface 266, a controller 268, and a transmitter 72. The information is communicated by means 76 to the receiver 74 of the hearing aid device 10. Once the information is received by the receiver 74, it is communicated to the control means 270 which also communicates with the local on/off control 190. The sound energy input is received at the microphone 184, and is converted into an electrical signal which is first amplified by the microphone transducer amplifier 260, then modified and amplified by the filter and intermediate gain amplifier 262, and is finally sent to a new amplifier element 278 which is a summation amplifier. The mechanical vibrations are sensed by the accelerometer 248, which converts the vibrations into an electrical signal. This electrical signal is received by the accelerometer transducer amplifier 272, which then outputs the signal to a gain amplifier stage 276. The control means 270 also communicates information to a volume control 274. Volume control 274 controls the gain of amplifier 276, however, the control means 270 also passes a signal to gain amplifier 276 which makes it possible for it to have reverse polarity . Polarity would be reversed in situations where the conductive sound picked up by the accelerometer 248 is to be attenuated. The output of th r v rsibl polarity

gain amplifier 276 is then communicated to the summation amplifier 278. At this point the accelerometer signal is either subtracted or added to the microphone signal. The output of summation amplifier 278 is then sent to the power amplifier 264 and then to the speaker element 100.

Another embodiment of the invention employs signal processing techniques to greatly enhance the performance of the invention for users with special hearing problems. In FIG. 14 there is a portable signal processing device 80, which can be either carried by hand or worn on the clothing (such as strapped to a belt) of the user. To adjust the volume and treble-base controls, the user inputs information through the operator interface 280, which can be a key pad, which information is then communicated to a controller 282. That information is then communicated to the radio frequency transmitter 82. This information would be in the form of digital signals which are then transmitted via communication means 90 to the receiver 86 of the hearing aid 10. At the hearing aid 10, sound energy is picked up by the microphone 184 and converted into electrical signals which are passed to the microphone transducer amplifier 260. The output of the transducer amplifier 260 is sent to a second radio frequency transmitter 88. This information is then communicated via communication means 90 to a second radio frequency receiver 84 which is located on the signal processing device 80. This information is communicated from the output of the receiver 84 to a signal processing controller 284. The signal processor 284 must work as nearly in real time as possible, to accept the audio information from the receiver 84 and then output th proc ssed audio

information in the form of an electrical signal to the radio frequency transmitter 82.

As is apparent to those skilled in the art, communication means 90 must be a full duplex means of communicating radio frequency information both to and from each device, the hearing aid 10 and the signal processing device 80. Once the signal is transmitted from the radio frequency transmitter 82 it is received by a radio frequency receiver 86 on the hearing aid device 10. The control portion of the received signal is a digital series of commands 286. These commands are communicated to the control means 270 which also communicates to a local on/off control 190. The audio portion of the received information which is received by radio frequency receiver 86 is an electrical signal 288. This audio signal is communicated to the filter and intermediate gain amplifier 262 which also communicates with the control means 270. The output of the filter and gain amplifier 262 is sent to the power amplifier 264 which outputs the signal to the speaker element 100.

An alternative embodiment of the invention which employs signal processing techniques is one that includes a self-contained enhanced signal processing controller within the hearing aid 10 itself. This embodiment is described in schematic form on FIG. 12, wherein the filter and intermediate gain amplifier 262 also contains the necessary signal processing controller to achieve the desired enhancement.

Another embodiment of the invention can consist of a radio receiver 94 which can receive either commercial broadcast or local broadcast. As illustrated in FIG. 15, this embodiment uses a

hand-held transmitter 70, which consists of the elements of the operator interface 266, the controller 268, and the output transmitter 72. Information from the transmitter 72 is communicated by means 76 to a receiver 74 on the hearing aid device 10. In this embodiment, the operator interface 266 can also control the frequency to be received at the hearing aid device 10 receiver 94. That information is transmitted by transmitter 72 via communication means 76 to the receiver 74. This information is subsequently communicated to the control means 270 and then to the tuner 290. The control means 270 also communicates with a local on/off control 190. Sound wave energy is received by the microphone 184 and is converted to an electrical signal which is communicated to the microphone transducer amplifier 260. The output of this transducer amplifier 260 is communicated to the filter and intermediate gain amplifier 262, whose output is then communicated to sound amplifier 278.

The hearing aid device 10 also receives radio frequency information via its receiver 94. Radio frequency receiver 94 can receive commercial broadcasts, for example, in the AM and FM bands of commercial communications, from a commercial transmitter 92 via communication means 96. In the case of a commercial transmitter, control means 270 transfers information to the tuner 290 which then controls which radio station will be received by the radio frequency receiver 94. The output of the receiver 94 is sent to a gain amplifier 276 whose gain is controlled by volume control 274 which communicates to the control means 270. The output of the gain amplifier 276 is then sent to the summation

amplifier 278 whos output consists of signals from both th microphon and th radio r ceiv r. The output of the summation amplifier 278 is communicated to the power amplifier 264 which then sends the signal to the speaker element 100. If the user so desires, radio frequency receiver 94 can receive a local broadcast which might consist of a miniature radio transmitter worn by the user which is broadcasting music, for example, from a compact disc player or from a cassette tape player. While such local radio transmitters may not be in use today, they are certainly foreseeable in the future, particularly after the present invention becomes common in the marketplace.

In summary, numerous benefits have been described which result from employing the concepts of the invention. The overall size, shape, and orientation of the hearing apparatus provide a package which fits deeply into the external auditory canal such that its microphone is placed at the acoustic focus of the concha, and its speaker is placed between the sigmoid portion of the canal and the tympanic membrane. Such placement of the speaker, along with sealing the air inside the external auditory canal around the hearing apparatus, achieves a closely-coupled system. The hearing apparatus can be used as a stand-alone device which includes all necessary signal-conditioning and amplification electronic circuitry, as well as enhanced signal processing, if so desired. The hearing apparatus also can be used in conjunction with a separate hand-held transmitter for controlling various operational functions, a separate enhanced signal processing device, if desired, or used in communication with a radio transmitter.

The foregoing description of a preferred embodiment of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Obvious modifications or variations are possible in light of the above teachings. The embodiment was chosen and described in order to best illustrate the principles of the invention and its practical application to thereby enable one of ordinary skill in the art to best utilize the invention in various embodiments and with various modifications as are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the claims appended hereto.

I CLAIM:

1. An apparatus adapted for use in a human external auditory canal with a tympanic membrane at its innermost terminus, the external auditory canal having a cartilaginous part with an innermost section of the cartilaginous part defining an S-shaped sigmoid portion, and a bony part that adjoins the sigmoid portion and extends to the tympanic membrane, the apparatus comprising:

(a) means for receiving energy in the form of sound waves;

(b) means for converting the received energy into an electrical signal;

(c) means for modifying said electrical signal; and

(d) means for converting said modified electrical signal into energy in the form of air-borne sound waves, said converting means being located in proximity to the tympanic membrane and configured and dimensioned to fit within the external auditory canal in a location between the sigmoid portion and the tympanic membrane.

2. An apparatus as recited in claim 1, wherein said means for converting sound wave energy into said electrical signal consists of a microphone.

3. An apparatus as recited in claim 2, wherein said micr phone is an electr t d vic .

4. An apparatus as recited in claim 2, wherein said microphone is a piezoelectric device.

5. An apparatus as recited in claim 1, wherein said modifying means includes a variable-gain amplifier.

6. An apparatus as recited in claim 5, wherein said variable-gain amplifier include an automatic gain control circuit.

7. An apparatus as recited in claim 6, wherein said automatic gain control circuit has a non-linear profile.

8. An apparatus as recited in claim 1, wherein said modifying means includes a variable-gain amplifier stage and a treble-bass filter stage.

9. An apparatus as recited in claim 1, wherein said means for converting said modified electrical signal into said sound wave energy includes a speaker having an elongated shape, said speaker having a vibration surface with a length greater than its width so as to be insertable into the bony part of the external auditory canal past the sigmoid portion of the cartilaginous part while having a surface area substantially as large as the surface area of the tympanic membrane.

10. An apparatus as recited in claim 9, wherein said speaker includes a rigid housing.

11. An apparatus as recited in claim 9, wherein said speaker further includes a rigid housing having

a transverse cross-sectional geom try of a flattened tube with th housing having a longitudinal axis, the longitudinal axis of the housing being adapted for placement in substantially parallel relationship with the longitudinal axis of the external auditory canal, the transverse cross-sectional dimension of the housing being smaller than the lumen of the external auditory canal.

12. An apparatus as recited in claim 9, wherein said speaker of elongated shape is mountable on a flexible articulation member.

13. An apparatus as recited in claim 12, wherein said flexible articulation member is rotatably flexible.

14. An apparatus as recited in claim 13, wherein said flexible articulation member is attached to an articulated joint.

15. An apparatus as recited in claim 9, wherein said speaker of elongated shape includes an electric motor having at least one reciprocially movable armature, said armature including of an oval-shaped coil and a speaker face membrane.

16. An apparatus as recited in claim 15, wherein said electric motor is linear.

17. An apparatus as recited in claim 15, wherein said electric motor includes at least one resonance cavity.

18. An apparatus as recited in claim 2, wherein

th apparatus is furth r adapt d for use in a human external auditory canal in which th outer portion of the cartilaginous part defines a bowl-shaped concha having an acoustic focus, and the microphone is located substantially at the acoustic focus of the concha when the modified signal converting means is located between the sigmoid portion and the tympanic membrane.

19. An apparatus as recited in claim 1, wherein said means for providing electric power consists of at least one battery.

20. An apparatus as recited in claim 1, further including means for preventing contamination of the modifying means and the modified signal converting means.

21. An apparatus as recited in claim 20, wherein said means for preventing contamination includes a disposable boot.

22. An apparatus as recited in claim 21, wherein said disposable boot includes a resiliently deformable material portion which seals and isolates the received energy converting means from the modified signal converting means in the user's ear.

23. A hearing aid, adapted for use in a human external auditory canal with a tympanic membrane at its innermost terminus, the external auditory canal having a cartilaginous part with an innermost section of the cartilaginous part defining an S-shaped sigmoid portion, a bony part that adjoins the sigmoid portion and ext nds to the tympanic membrane, the

outer section of th cartilaginous part defining a bowl-shaped concha having an acoustic focus, the hearing aid comprising:

(a) a microphone, located at the acoustic focus of the concha, said microphone being operative to convert sound waves into a microphone electrical signal;

(b) an accelerometer for producing an accelerometer electrical signal in response to and representative of the bone-conducted portion of the user's speech;

(c) electronic circuit means for selectively modifying said microphone and accelerometer electrical signals and creating a joint electrical signal;

(d) a speaker shaped and dimensioned to be located in the external auditory canal between the sigmoid portion of the cartilaginous part of the external auditory canal and the tympanic membrane, said speaker being operative to convert said joint electrical signal into sound waves; and

(e) a self-contained D.C. power supply, providing electrical power to said electronic circuit means.

24. A hearing aid as recited in claim 23, wherein said accelerometer is constructed of a charged membrane having a first fixed portion and a second movabl portion, and a mass mount d upon the second

movable portion.

25. A hearing aid as recited in claim 23, wherein said accelerometer is constructed of a piezoelectric beam having a first fixed portion and a movable second portion, and a mass mounted upon the second movable portion.

26. A hearing aid as recited in claim 23, wherein said accelerometer is constructed of a strain gauged beam having a first fixed portion and a movable second portion, and a mass mounted upon the second movable portion.

27. A hearing aid as recited in claim 23, wherein said accelerometer is formed as an integrated unit on a substrate.

28. A hearing aid as recited in claim 23, further comprising an ON-OFF switch.

29. A hearing aid as recited in claim 28, wherein said ON-OFF switch functions in a rotatable manner.

30. A hearing aid as recited in claim 23, wherein said electronic circuit means includes a signal conditioning amplifier having an FET input stage.

31. A hearing aid as recited in claim 23, wherein said electronic circuit means includes a signal conditioning amplifier having a bipolar input stage.

32. A hearing aid as recited in claim 23, wherein said electronic circuit means includes an input stag , a gainshaping filter network stage, and an output driving stage.

33. A hearing aid as r cited in claim 23, further comprising m ans for receiving and demodulating control signals, said electronic circuit means being responsive to said demodulated control signals.

34. A hearing aid as recited in claim 33, further comprising:

(i) a portable transmitter which communicates with said receiving and demodulating means, said portable transmitter including an operator interface for entering gain and filtering parameters of the microphone and accelerometer electrical signals;

(ii) a controller for communicating with said operator interface and creating a command electrical signal;

(iii) an output stage for modulating said command electrical signal and creating a control signal for said receiving and demodulating means, said control signal being transmitted via carrier wave to said receiving and demodulating means; and

(iv) a self-contained D.C. power supply, providing electrical power to said operator interface and controller, and to said output transmitter stage.

35. A hearing aid, comprising:

(a) a microphone for receiving and converting sound waves into a repres ntative el ctrical signal;

(b) a signal proc ssing circuit;

(c) means for communicating said representative electrical signal to said signal processing circuit, said signal processing circuit being operative to enhance the representative electrical signal and create a processed signal;

(d) a radio transmitter, said transmitter modulating the processed signal and creating a modulated processed signal, the transmitter outputting the modulated processed signal via carrier wave;

(e) a radio receiver adapted for positioning within the human ear for receiving and demodulating the modulated processed signal;

(f) signal conditioning means for conditioning said demodulated processed signal; and

(g) a speaker responsive to said conditioned processed signal, said speaker converting the conditioned processed signal into sound waves.

36. A hearing aid as recited in claim 35, wherein said microphone is adapted for positioning in the human ear, and said communicating means includes a second radio transmitter adapted for positioning in the human ear and a second radio receiver adapted for positioning external to the human ear, the signal processing circuit being responsive to said second radio rec iver.

37. A h aring aid comprising:

a) a microphone for receiving and converting sound waves into a representative microphone electrical signal;

b) an accelerometer adapted for placement proximal to a user's ear, the accelerometer being responsive to a user's bone-conducted speech for creating a representative accelerometer electrical signal;

c) signal processing means for creating a processed signal which is dependent upon both the microphone and accelerometer electrical signals, at least a portion of the signal processing means being adapted for placement distal to the user's ear;

d) a radio transmitter, said transmitter modulating the processed signal and creating a modulated processed signal, the transmitter outputting the modulated processed signal via carrier wave;

e) a radio receiver adapted for positioning proximal to the user's ear for receiving and demodulating the modulated processed signal;

f) signal conditioning means for conditioning said demodulated processed signal; and

g) a speaker responsive to said conditioned proc ss d signal, said speaker c nverting the c nditioned process d signal into sound wav s.

38. A hearing aid as recited in claim 37, wherein the signal processing means includes means for modifying the microphone and accelerometer electrical signals and creating a joint electrical signal, a second radio transmitter for modulating and transmitting the joint electrical signal; a second radio receiver for receiving and demodulating the joint electrical signal; and means for enhancing the demodulated joint electrical signal.

39. A hearing aid as recited in claim 37, wherein the signal processing means includes a second radio transmitter for modulating and transmitting the accelerometer electrical signal, a second radio receiver for receiving and demodulating the accelerometer electrical signal, means for combining the accelerometer electrical signal with the microphone electrical signal to form a joint signal; and means for enhancing the joint signal.

40. A hearing aid comprising:

(a) a microphone, said microphone being operative to convert sound waves into a microphone electrical signal;

(b) an accelerometer for producing an accelerometer electrical signal in response to and representative of the bone-conducted portion of the user's speech;

(c) electronic circuit means for selectively modifying said microphone and accelerometer electrical signals and creating a joint electrical signal;

(d) a speaker, said speaker being perative to convert said joint lectrical signal into sound waves; and

(e) a self-contained D.C. power supply, providing electrical power to said electronic circuit means.

41. A hearing aid as recited in claim 40, wherein said accelerometer is constructed of a charged membrane having a first fixed portion and a second movable portion, and a mass mounted upon the second movable portion.

42. A hearing aid as recited in claim 40, wherein said accelerometer is constructed of a piezoelectric beam having a first fixed portion and a movable second portion, and a mass mounted upon the second movable portion.

43. A hearing aid as recited in claim 40, wherein said accelerometer is constructed of a strain gauged beam having a first fixed portion and a movable second portion, and a mass mounted upon the second movable portion.

44. A hearing aid as recited in claim 40, wherein said accelerometer is formed as an integrated unit on a substrate.

45. A hearing aid as recited in claim 40, further comprising means for receiving and demodulating control signals, said electronic circuit means being responsive to said demodulated control signals.

46. An apparatus adapted for use in a human external auditory canal with a tympanic membrane at its innermost terminus, the external auditory canal having a cartilaginous part with an innermost section of the cartilaginous part defining an S-shaped sigmoid portion, and a bony part that adjoins the sigmoid portion and extends to the tympanic membrane, the apparatus comprising:

(a) means for receiving radio-frequency energy;

(b) means for converting the received energy into an electrical signal;

(c) means for modifying said electrical signal; and

(d) means for converting said modified electrical signal into energy in the form of air-borne sound waves, said converting means being located in proximity to the tympanic membrane and configured and dimensioned to fit within the external auditory canal in a location between the sigmoid portion and the tympanic membrane.

AMENDED CLAIMS

[received by the International Bureau
on 25 May 1992 (25.05.92);
original claims 1,2,12,15,17 and 20 amended;
other claims unchanged (5 pages)]

1. An apparatus adapted for use in a human external auditory canal with substantially non-compliant side walls and a compliant tympanic membrane at its innermost terminus, the external auditory canal having a cartilaginous part with an innermost section of the cartilaginous part forming an S-shaped sigmoid portion, and a bony portion that extends to the tympanic membrane, the apparatus comprising:

(a) means for receiving energy in the form of sound waves and converting the received energy into an electrical signal;

(b) means for modifying said electrical signal;

(c) means for converting said modified electrical signal into energy in the form of air-borne sound waves, said converting means including an active compliance surface having a functional area comparable to that of the tympanic membrane for creating said airborne sound waves, said compliant surface being located in proximity to the tympanic membrane and being configured and dimensioned to fit at least partially within the external auditory canal in a location between the sigmoid portion and the tympanic membrane; and

(d) means for acoustically isolating the inner and external portions of the auditory canal along with the substantially non-compliant side walls and such that the compliance surface of the converting means and the compliant tympanic membrane along with the non-compliant walls of the auditory canal form a closed cavity.

2. An apparatus as recited in claim 1, wherein said means for receiving energy and converting the received energy into an electrical signal includes a microphone.

3. An apparatus as recited in claim 2, wherein said microphone is an electret device.

a transverse cross-sectional geometry of a flattened tube with the housing having a longitudinal axis, the longitudinal axis of the housing being adapted for placement in substantially parallel relationship with the longitudinal axis of the external auditory canal, the transverse cross-sectional dimension of the housing being smaller than the lumen of the external auditory canal.

12. An apparatus as recited in claim 1, further including a speaker having an electric motor and at least one reciprocably moveable armature, said armature including a coil and a speaker face membrane, said speaker being rotatably mounted on a articulation and member.

13. An apparatus as recited in claim 12, wherein said flexible articulation member is rotatably flexible.

14. An apparatus as recited in claim 13, wherein said flexible articulation member is attached to an articulated joint.

15. An apparatus as recited in claim 1, further including a speaker having an electric motor and at least one reciprocably movable armature, said armature including a coil and a speaker face membrane.

16. An apparatus as recited in claim 15, wherein said electric motor is linear.

17. An apparatus as recited in claim 15, wherein said electric motor includes at least one resonance cavity on the opposite side of the compliance surface

of the converting means relative to the tympanic membrane.

18. An apparatus as recited in claim 2, wherein

the apparatus is further adapted for use in a human external auditory canal in which the outer portion of the cartilaginous part defines a bowl-shaped concha having an acoustic focus, and the microphone is located substantially at the acoustic focus of the concha when the modified signal converting means is located between the sigmoid portion and the tympanic membrane.

19. An apparatus as recited in claim 1, wherein said means for providing electric power consists of at least one battery.

20. An apparatus as recited in claim 1, further including means for preventing biological contamination of the modifying means and the modified signal converting means.

21. An apparatus as recited in claim 20, wherein said means for preventing contamination includes a disposable boot.

22. An apparatus as recited in claim 21, wherein said disposable boot includes a resiliently deformable material portion which seals and isolates the received energy converting means from the modified signal converting means in the user's ear.

23. A hearing aid, adapted for use in a human external auditory canal with a tympanic membrane at its innermost terminus, the external auditory canal having a cartilaginous part with an innermost section of the cartilaginous part defining an S-shaped sigmoid portion, a bony part that adjoins the sigmoid portion and extends to the tympanic membrane, the

## STATEMENT UNDER ARTICLE 19

Claims 1, 2, 12, 15 and 17 have been amended to add limitations not present in these claims as originally filed, and to more clearly distinguish over the prior art of record. No claims have been cancelled.




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 2




FIG. 3A




FIG. 3B

FIG. 4A



FIG. 4B






FIG. 5A




FIG. 5C




FIG. 5B




FIG. 6A




FIG. 6B


FIG. 6C




FIG. 7A




FIG. 7C




FIG. 7B




FIG. 8A




FIG. 8C




FIG. 8B




FIG. 9A




FIG. 9C




FIG. 9B

FIG. 10A




FIG. 10 B

FIG. 11






FIG. 12

FIG. 13


10
100
264
190
278
Σ
74
270
262
276
274
76
260
272
72
268
266
70
184
248


10
100
190
264
270
262
286
86
288
80
82
90
88
282
284
260
280
84
184

FIG. 14

FIG. 15


10
100
264
190
278
Σ
74
270
262
274
276
76
260
72
268
266
184
290
94
96
92
70

# INTERNATIONAL SEARCH REPORT

International Application No. PCT/US92/00380

## I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) [6]

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC(5): H04R 25/00;
US CL : 381/68,68.2-69.4,68.6,69; 600/25; 128/420.5,420.6

## II. FIELDS SEARCHED

Minimum Documentation Searched [7]

| Classification System | Classification Symbols |
|---|---|
| U.S. | 381/68,68.2-68.4,68.6,69,151,110,122,186,203; 181/130,135<br>128/420.5,420.6; 600/25 |

Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in the Fields Searched [8]

## III. DOCUMENTS CONSIDERED TO BE RELEVANT [9]

| Category [10] | Citation of Document, [11] with indication, where appropriate, of the relevant passages [12] | Relevant to Claim No. [13] |
|---|---|---|
| X<br>Y | US, A, 3,527,901 (GEIB) 08 SEPTEMBER 1970<br>See the entire document. | 1,2,19-22,46<br>3-18,23-33 |
| X<br>Y | US, A, 4,901,354 (GOLLMAR) 13 FEBRUARY 1990<br>See col. 2, line 63 through column 3, line 44. | 40<br>23-32,41-44 |
| X<br>Y | US, A, 3,746,789 (ALCIVAR) 17 JULY 1973<br>See column 1, line 62 through column 5, line 55. | 40,45<br>23,33 |
| Y | US, A, 4,622,692 (COLE) 11 NOVEMBER 1986<br>See column 3, line 14 through column 4, line 31. | 3-8,18 |
| Y | US, A, 3,873,784 (DOSCHEK) 25 MARCH 1975<br>See figs. 18,27,38. | 9-12,13-17 |
| Y | US, A, 4,920,570 (WEST) 24 APRIL 1990<br>See the entire document. | 35,36 |
| Y | US, A, 4,334,315 (ONO) 08 JUNE 1982<br>See fig. 12. | 35,36 |
| Y | US, A, 4,150,262 (ONO) 17 APRIL 1979<br>See fig. 12. | 24-27,41-44 |

* Special categories of cited documents: [10]

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search

19 FEBRUARY 1992

Date of Mailing of this International Search Report

25 MAR 1992

International Searching Authority

ISA/US

Signature of Authorized Officer

JASON CHAN

Form PCT/ISA/210 (second sheet) (Rev. 11-87)

FURTHER INFORMATION CONTINUED FROM THE SEC ND SHEET

| | | |
|---|---|---|
| Y | US, A, 4,880,076 (AHLBERG) 14 NOVEMBER 1989<br>See column 5, lines 16-27. | 13,14 |
| Y | US, A, 4,329,676 (McDONALD) 11 MAY 1982<br>See column 6, lines 1-4. | 29 |
| Y | US, A, 4,068,090 (KOMATSU) 10 JANUARY 1978<br>See column 8, lines 41-42 and fig. 12. | 30-32 |

## V. ☐ OBSERVATIONS WHERE CERTAIN CLAIMS WERE FOUND UNSEARCHABLE [1]

This international search report has not been established in respect of certain claims under Article 17(2) (a) for the following reasons:

1. ☐ Claim numbers because they relate to subject matter [2] not required to be searched by this Authority, namely:

2. ☐ Claim numbers . because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out [3], specifically:

3. ☐ Claim numbers_____, because they are dependent claims not drafted in accordance with the second and third sentences of PCT Rule 6.4(a).

## VI. ☐ OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING [4]

This International Searching Authority found multiple inventions in this international application as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims of the international application.

2. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims of the international application for which fees were paid, specifically claims:

3. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claim numbers:

4. ☐ As all searchable claims could be searched without effort justifying an additional fee, the International Searching Authority did not invite payment of any additional fee.

Remark on Protest

☐ The additional search fees were accompanied by applicant's protest.

☐ No protest accompanied the payment of additional search fees.